WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Well No 2.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5651
Rec. JAN. 25 1961
Well No.
Permit No. 18869
Do not fill in 53742

Owner: Joe Peretti
Address: Carlin Nev
Driller: Enlow Drilling Co
Address: Susanville Lic. No. 249

Location of well: NE ¼ NW ¼ Sec. 29, T. 29 N/S, R. 57 E, in Elko County

or

Water will be used for: Irrigation
Total depth of well: 575

Size of drilled hole: 26
Weight of casing per linear foot: 44

Thickness of casing: 3/16
Temp. of water:

Diameter and length of casing: 575
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 5'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Oct 1 - 60
Date of completion of well: Nov 15 - 60

Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Clay & Soil
20	34	14	Gravel & Clay
34	65	31	Boulders & Gravel
65	255	190	Clay - Gravel & Boulders
255	268	13	Fine Gravel & Sand
268	291	23	Gravel & Boulders
291	345	54	Clay & Gravel
345	375	30	Gravel - Sand - Boulders
375	407	32	Sandy Clay
407	415	8	Gravel & Sand
415	500	85	Clay & Shales
500	529	29	Sand & Gravel
529	575	46	Clay - Sand - Boulders

Replaced by Well log 121659
PLUGGED BY LOG 124423

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 34 to 65 ft.

Other aquifers (255 - 268)
(345 - 375)
(407 - 415)
(500 - 529)

First water at 30' feet.

Casing perforated
from 40' to 575' ft.

Size of perforations
3/16 x 2 - Factory

919