

Need
copy

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5-659
 Rec. 1-31-61
 Well No. 17731
 Permit No. 19731
 Do not alter

Owner: Floyd D. Switzer Driller: Effinger Drill & Pump
 Address: 5109 Alta Drive Address: 5488 West Duncan Drive Lic. No. 21
 Location of well: NE 1/4 NE 1/4 Sec. 26, T. 21N/S, R. 61E, in Clark County
 or: Bond Road Permit 19731
 Water will be used for: Domestic Qm Total depth of well: 300 feet
 Size of drilled hole: 8 inch Weight of casing per linear foot: _____
 Thickness of casing: 10 Gauge Temp. of water: _____
 Diameter and length of casing: 6" ID Liner
(Casing 12" in diameter and under give inside diameter; casing 12" to diameter give inside diameter)
 If flowing well give flow in c.f.s. or g.p.m. and pressure: _____
 If nonflowing well give depth of standing water from surface: Flowing 100ft
 If flowing well describe control works: Sanitary Seal
(Type and size of valve, etc.)
 Date of commencement of well: December 16, 1960 Date of completion of well: December 19, 1960
 Type of well rig: "71 Speed Star"

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|---|
| | | | Well drilled for John Angus September 26, 1955 by Effinger Drill & Pump |
| 140 | 155 | 15 | Red Clay |
| 155 | 170 | 15 | Yellow Clay |
| 170 | 185 | 15 | Gravel (Water) |
| 185 | 204 | 19 | Sandstone |
| 204 | 215 | 11 | Sand |
| 215 | 222 | 7 | Red Clay |
| 222 | 240 | 18 | Limestone (Water) |
| 240 | 245 | 5 | Red Clay |
| 245 | 250 | 5 | Sandstone (Water) |
| 250 | 270 | 20 | Red Clay |
| 270 | 293 | 23 | Gravel (Water) |
| 293 | 300 | 7 | Red Clay |

Water bearing Formation, Casing perforations, Etc.

Chief aquifer (water-bearing formation)
 from 270 to 293 ft.

Other aquifers: 245-250
222-240
170-185

First water at _____ feet.

Casing perforated
 from _____ to _____ ft.

Size of perforations
Perforated Liner

