


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5665
 Rec. Feb. 2 1961
 Well No.
 Permit No. 20021



*Do not fill in
Basin #102*

Owner Standard Slag Driller Bob Meyer
 Address Gabbs Nevada Address Hot Springs Rd. Lic. No. 209

Location of well: nw 1/4 se 1/4 Sec. 9, T. 14N/S, R. 23E, in Lyon County
 or 6M: South South of Standard Slag

Water will be used for Minning Total depth of well 85 ft.

Size of drilled hole 6 in. Weight of casing per linear foot 13#

Thickness of casing .188 Temp. of water cool

Diameter and length of casing 6 in. by 85 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing

If nonflowing well give depth of standing water from surface 15 ft.

If flowing well describe control works Not Flowing
 (Type and size of valve, etc.)

Date of commencement of well Jan. 9, 1961 Date of completion of well Jan. 30, 1961

Type of well rig 71 Speed Star

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	53	53	Old well
53	56	6	Sanded 14
56	61	5	Hard Rock
61	70	9	Sand & gravel
70	80	10	White clay & Rock
80	85	5	Rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 61 to 70 ft.

Other aquifers.....

First water at 61 feet.

Casing perforated from 4 ft. to 85 ft. ft.

Size of perforations
Mills 3/8 by 2

Handwritten notes and signatures in the bottom left area of the log.

