Same as 5626.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5707
Rec. Feb 20 1961
Well No.
Permit No.
Do not fill in

Owner: Thomas Clay Driller: Darell Lee

Address: 1001 Panaca, Caliente Nevada Address: Pioche Nevada Lic. No. 30

Location of well: NW¼ SW¼ Sec. 25, T. 2 N/S, R. 67 E, in Lincoln County

or

Water will be used for: Irrigation Total depth of well: 135'

Size of drilled hole: 14" 115' 10" 20' Weight of casing per linear foot:

Thickness of casing: 10 gauge Temp. of water:

Diameter and length of casing: 14" 100'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 27' 6"

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: December 23, 1960 Date of completion of well: February 11, 1961

Type of well rig: Cable Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	77	77	sandy clay
77	90	13	gravel
90	135	45	clay - Panaca bed

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 77 to 90 ft.

Other aquifers:

First water at 30 feet.

Casing perforated
from 34 to 100 ft.

Size of perforations
1/8 x 1 1/2"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Gravel pack hole 10" 85'
Well test by Alex Wood - Beryl, Utah
500 g.p.m. at 70'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Darrell Free
Well Driller

By Owner

License No. 30

Dated Feb 14, 1961

(Not to be filled in by Driller)

1961 FEB 20 AM 9 39
STATE ENGINEER
OFFICE