

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5720
 Rec. Mar. 9 1956
 Well No. _____
 Permit No. 323
Do not fill in

Owner Walter Bates Davis Maylor Driller S. R. McKinney & Son

Address 1200 Nellis Blvd. Las Vegas Address 1042 S. Main Las Vegas No. 45

Location of well: SW 1/4 NW 1/4 Sec. 28, T. 20 N/S, R. 62 E, in Clark Count
or Commercial

Water will be used for Domestic (Bar) Pump Total depth of well 100 ft

Size of drilled hole 12" to 50 ft, 10" to 100 Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water _____

Diameter and length of casing 8" I.D. to 100 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 28 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well March 27, 1956 Date of completion of well March 27, 1956

Type of well rig Bucyrus Erie 24 L. Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	32	32	brown clay
32	35	3	brown sand water
35	50	15	brown sandy clay
50	54	4	brown sand water
54	65	11	brown clay
65	72	7	brown sand wafer
72	83	11	brown clay
83	89	6	brown sand water
89	100	11	brown clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 83 to 89 ft.

Other aquifers 65 to 72

50 to 54

First water at 32 feet.

Casing perforated

from 60 to 100 ft.

Size of perforations

3/16" X 10"

