

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5813
 Rec. April 6 1961
 Well No. _____
 Permit No. _____
Do not fill in

Owner Carl W. Stevens Driller Tholke & Petersen

Address 1035 Cornell st. Lovelock Nev. Address P.O. Box 663 Sparks Nev. Lic. No. 334

Location of well: NE 1/4 Sec 29, T. 10N/S, R. 21E, in Douglas County

Water will be used for Domestic Use Total depth of well 91 ft.

Size of drilled hole 6-5/8" Weight of casing per linear foot 10.9

Thickness of casing 3/16" Temp. of water 72 Degrees

Diameter and length of casing 6 1/2" I.D. 22' Lengths installed to 91 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 20 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 12/15/60 Date of completion of well 12/20/61

Type of well rig 29T Buggy's Fire WALK Cabae Tool Rig.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top soil
2	10	8	Clay with gravel
10	91	81	Solid granite with sand seams about 5ft. apart. Water was in sand seams

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 30ft. to 91ft. ft.

Other aquifers Water was in sand seams starting at 30 ft. and increasing in volume as hole was deeper- to 10 gal. per.

First water at 20 ft. feet.

Casing perforated

from 20 ft. to 91 ft. ft.

Size of perforations

3/16" slits 5" long



