

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5815
 Rec. APRIL 6 1961
 Well No. _____
 Permit No. _____
Do not fill in

Owner Frank W. Rowe Driller Tholke & Petersen
 Address 823 Sullivan Lane Sparks, Nev. Address Box 663 Sparks, Nev. Lic. No 334
 Location of well: NE 1/4, N 1/2 Sec 34, T 20N/S, R 20E, in Washoe County
 or Spanish Springs area
 Water will be used for domestic Total depth of well 50 ft.
 Size of drilled hole 6 5/8 Weight of casing per linear foot 5.3
 Thickness of casing 3/16" Temp. of water cold
 Diameter and length of casing 6 5/8 O.D. to ~~bottom~~ bottom of hole
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure. _____
 If nonflowing well give depth of standing water from surface 25 ft.
 If flowing well describe control works. _____
(Type and size of valve, etc.)
 Date of commencement of well 2/12/61 Date of completion of well 2/13/61
 Type of well rig Cable tool drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top soil
2	15	13	Clay
15	50	25	Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 15 to 50 ft.

Other aquifers water bearing sand

First water at 15 feet.

Casing perforated

from 10 to 50 ft.

Size of perforations

3/16 slits on 9" senters 4" long



