

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Lic. 5-5760

Log No. 3830  
 Rec. APRIL 21 1961  
 Well No. \_\_\_\_\_  
 Permit No. PETERSEN  
Do not fill in

THOLKT  
 Well Drilling

Owner Sears and Roebuck - D. Klinefelter Driller WATER WELLS A. D. LIST WELLS

Address Reno, Nevada Address \_\_\_\_\_ Lic. No. 334

Location of well: 1/4 1/4 Sec. 14., T. 15 N/S, R. 20 E, in Ormsby P. O. Box 253 County Spartan, Nevada

Water will be used for Domestic Total depth of well 95 ft.

Size of drilled hole 6 5/8 Weight of casing per linear foot 188 ga.

Thickness of casing 3/16" Temp. of water cold

Diameter and length of casing 6 5/8 O.D. set to bottom 95 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_

If nonflowing well give depth of standing water from surface. \_\_\_\_\_

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 3/25/61 Date of completion of well 3/27/61

Type of well rig Bucyrus cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	top soil
5	25	20	firm D.G.
20	80	60	water bearing D.G.
80	95	15	course sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 60 to 95 ft.

Other aquifers \_\_\_\_\_

First water at \_\_\_\_\_ feet.

Casing perforated

from 50 to 95 ft.

Size of perforations

torch 3/16 4" long

