

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5831
 Rec. April 21 19 61
 Well No.
 Permit No.
Do not fill in

THOLKE & PETERSEN

Owner Sears Roebuck and Co Driller F Hensen Well Drilling

Address Reno Address WATER WELLS AND TEST WELLS Lic. No.

Location of well: SE 1/4 SW 1/4 Sec 32, T14 N/S, R. 20E, in Douglas County

or P. O. Box 663
Sparks, Nevada

Water will be used for Domestic Total depth of well 59 ft.

Size of drilled hole 6 5/8 Weight of casing per linear foot 188 ga.

Thickness of casing 3/16/ Temp. of water cold

Diameter and length of casing 6 5/8 O.D. set 59 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 5 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 3/24/61 Date of completion of well 3/24/61

Type of well rig Bucyrus cable tool drill

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|---------------------|
| 0 | 10 | 10 | Sandy top soil |
| 10 | 15 | 5 | Sand and pea gravel |
| 15 | 59 | 44 | Fine sand |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 15 to 59 ft.

Other aquifers

First water at 15 feet.

Casing perforated

from 38 to 59 ft.

Size of perforations

Torch 3/16 4" long



