

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5899
 Rec. MAY 22 19 61
 Well No.
 Permit No.

Do not fill in

Owner Iris B. Fox Driller Reno Pump & Supply

Address 2300 Prater Way - Sparks, Nev. Address 7468 So. Virginia - Reno No. 295

Location of well: SW 1/4 NW 1/4 Sec. 21., T. 19. N/S, R. 20. E, in Washoe County
 or Lot 1, Block B, Rindfliesch Subdivision

Water will be used for Domestic Total depth of well 55'

Size of drilled hole 6" Weight of casing per linear foot

Thickness of casing 12 Ga. Temp. of water Cold

Diameter and length of casing 6" x 55'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure 2 G.P.M.

If nonflowing well give depth of standing water from surface

If flowing well describe control works Sanitary Seal with 1" line and 1" gate valve.
(Type and size of valve, etc.)

Date of commencement of well 5/18/60 Date of completion of well 5/21/60

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top soil
2	38	36	Clay, sand, gravel; surface water here.
38	41	3	Blue silt
41	56	15	Sand, gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 41 to 56 ft.

Other aquifers

See Log

First water at 2 feet.

Casing perforated

from 41 to 55 ft.

Size of perforations

1/16" x 1"

