

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 5897
 Rec. MAY 22 19 61
 Well No.
 Permit No.

Do not fill in

Owner Gerald Norman Driller Reno Pump & Supply

Address 795 Twin Lakes Dr. - Reno, Nev. Address 7468 So. Virginia - Reno Lic. No. 295

Location of well: NW 1/4 SW 1/4 Sec. 16, T. 19 N/S, R. 19 E, in Washoe County

Water will be used for Domestic Total depth of well 171'

Size of drilled hole 6" Weight of casing per linear foot.....

Thickness of casing 12 Ga. Temp. of water Cold

Diameter and length of casing 6" x 171'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 122'

If flowing well describe control works.....
 (Type and size of valve, etc.)

Date of commencement of well 8/19/60 Date of completion of well 8/25/60

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	48	48	Cemented Rock & Gravel
48	61	13	Sand, Gravel, Clay
61	69	8	Hard Pan
69	77	8	Sandy Brown Clay
77	81	4	Tight Gravel (3 GPM water)
81	135	54	Sandy Brown Clay
135	146	11	Hard Pan
146	155	9	Clay
155	169	14	Gravel & Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 155' to 169' ft.

Other aquifers.....

See Log

First water at 79 feet.

Casing perforated

from 139 to 167 ft.

Size of perforations

1/16" x 1"



