19207

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5917
Rec. June 7 1961
Well No.
Permit No. 19207
Do not fill in

Owner: Elsie Groninger Driller: Lennox L. Mauldin

Address: % Dalton Ford, Battle Mountain, Nev. Address: Box 583, Beowawe, Nev. Lic. No. 340

Location of well: SE corner SE ¼ SE ¼ Sec. 9, T. 25 N., R. 42 E., in Lander County, County

or

Water will be used for: irrigation Total depth of well: 200 ft.

Size of drilled hole: 16" Weight of casing per linear foot

Thickness of casing: 10 gauge Temp. of water: cold

Diameter and length of casing: 16" 4 ft. lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 78 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: April 3 Date of completion of well: May 20

Type of well rig: 71 Star

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1'	8'	8'	Top soil - sandy loam
8'	48'	40'	gravel & sand
48'	60'	12'	clay
60'	80'	20'	clay and gravel
80'	200'	120'	water bearing medium gravel and sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 80' to 200' ft.

Other aquifers: NONE

First water at 80 feet.

Casing perforated
from 80' to 200' ft.

Size of perforations
3/8" wide 5/8" long

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16"	1'	200'	4'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well was Not test pumped by me
Water was Not tested

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Lennon L. Mauldin
Well Driller

By.....

License No. 340

Dated May 29, 19 61

(Not to be filled in by Driller)

1961 MAY 31 AM 8 58

STATE ENGINEER