

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5932  
 Rec. June 15 1961  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Ethelyn Coverston Driller J. B. Reynolds

Address Fallon Address Fallon Lic. No. 28

Location of well: SW 1/4 NE 1/4 Sec. 32, T. 19 N, R. 28 E, in Churchill County

Water will be used for domestic Total depth of well 111'

Size of drilled hole 6" Weight of casing per linear foot 12 lb.

Thickness of casing .183 Temp. of water cold

Diameter and length of casing 6" x 111'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 16'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 3/25/60 Date of completion of well 3/29/60

Type of well rig cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	silt & sand
28	35	7	sandy clay
35	41	6	coarse sand
41	62	21	blue sand & clay
62	70	8	coarse sand
70	93	23	blue clay & sand
93	98	5	brown clay
98	109	11	coarse sand
109			blue clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 98 to 109 ft.

Other aquifers \_\_\_\_\_  
none in use

First water at 16 feet.

Casing perforated  
 from 101 to 111 ft.

Size of perforations  
1/4" x 2"



