LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8	0	185	185	Gravel packed

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Baker test - 20 gals. per min

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Gene Peterson
Well Driller

By

License No. 334

Dated May 6, 1961

(Not to be filled in by Driller)

1961 JUN 26 AM 10 45

STATE ENGINEER

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5952
Rec. JUNE 26 1961
Well No.
Permit No.
Do not fill in

Owner Wm W Tholke Driller GW Peterson

Address Sun Valley Address Box 663 Sparks Lic. No. 334

Location of well: SE ¼ ¼ Sec. 30, T 20 N/S, R 20 E, in Washoe County

or

Water will be used for Domestic Total depth of well 185

Size of drilled hole 6 5/8 Weight of casing per linear foot 1.63

Thickness of casing .188 ga. Temp. of water cold

Diameter and length of casing 6 1/4
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 25'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 5/1/61 Date of completion of well 5/5/61

Type of well rig Bucyrus cable tool drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	top soil
2	50	48	clay and gravel
50	60	10	sand and gravel
60	100	40	clay
100	150	50	D.G.
150	185	35	sand and clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 50 to 185 ft.

Other aquifers

First water at 50 feet.

Casing perforated

from 50 to 185 ft.

Size of perforations

3/16 torch

(OVER)

919