

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5953  
 Rec. JUNE 26 1961  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Tony Maderos Driller Gu Peterson ✓  
 Address San Valley Address Box 663 Sparks Lic. No. 334  
 Location of well: Sw 1/4 Sw 1/4 Sec 14, T 20N/S, R 20E, in Washoe County

Water will be used for Domestic Total depth of well 337

Size of drilled hole 6 5/8 Weight of casing per linear foot 1.63

Thickness of casing 0.188 ga Temp. of water cold

Diameter and length of casing 6 5/8 O.D. - 330 ft  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_

If nonflowing well give depth of standing water from surface 300

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 5/6/61 Date of completion of well 5/10/61

Type of well rig Cable tool drill

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	Top soil
1	130	129	clay
130	150	20	clay with lava rock
150	200	50	clay - (white)
200	260	60	clay - (blue)
260	300	40	bluish granitic
300	337	37	crystal sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 300 to 337 ft.

Other aquifers \_\_\_\_\_

First water at 300 feet.

Casing perforated

from 275 to 330 ft.

Size of perforations

torch



