

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6037
 Rec. JULY 31 1961
 Well No.
 Permit No.

Do not fill in

Owner IRVIN Puetz Driller LENNOX L. MAULDIN

Address Carlin Nevada Address Box 583, Beowawe, Nev. Lic. No. 340

Location of well: NE 1/4 1/4 Sec. 26, T. 33N R. 52E, in E1K0 County

Water will be used for Stock water Total depth of well 130 ft.

Size of drilled hole 12" Weight of casing per linear foot

Thickness of casing 10 gauge Temp. of water cold

Diameter and length of casing 12" 4 ft. lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 8 ft. 4 in.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well JUNE 21 Date of completion of well JUNE 26

Type of well rig 71 STAR

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	6	6	top soil
6	8	2	Hard clay and gravel
8	12	4	water bearing gravel
12	20	8	clay
20	22	2	water bearing gravel
22	130	108	clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 8 to 12 ft.

Other aquifers 20 to 22

water bearing gravel

First water at 8 feet.

Casing perforated

from 4 to 24 ft.

Size of perforations

factory perforated



