


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 6055
 Rec. Final 19 61
 Well No. 1
 Permit No. 77480 23667
Do not fill in

Owner Garms Properties Driller Enloe Drilling Co.

Address Smith, Nevada Address Carson City, Nevada Lic. No. 249

Location of well: SE 1/4 SE 1/4 Sec. 28, T. 11 N/S, R. 24 E, in Lyon County

Water will be used for Irrigation Total depth of well 454'

Size of drilled hole 24" Weight of casing per linear foot 38#

Thickness of casing 1/4" Temp. of water 59° F.

Diameter and length of casing 16" 454'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface..... 45'

If flowing well describe control works.....
 (Type and size of valve, etc.)

Date of commencement of well 3/16/61 Date of completion of well 4/5/61

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	24	24	Sand, gravel & Clay
24	40	16	Sand, gravel & clay
40	46	6	Course sand
46	114	68	Sand, gravel & clay
114	120	6	Large boulders
120	125	5	Fine sand
125	138	13	Clay
138	158	20	Sand & clay
158	169	11	Hard packed clay
169	177	18	Boulders & clay
177	180	3	Boulders & clay
180	196	16	Soft clay
196	204	18	Rock
204	220	16	Sand rock
220	226	6	Soft fine sand
226	245	19	Sand & clay
245	249	4	Soft sandy clay
249	271	28	Soft sandy clay
271	294	23	Boulders & clay
294	304	10	Large boulders
304	337	33	Hard rock
337	350	13	Sand gravel & clay
350	395	45	Sand gravel & clay
395	406	11	Sand gravel & clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 304 to 337 ft.

Other aquifers 406 - 451

451 - 474

First water at 73' feet.

Casing perforated

from 140 to 474 ft.

Size of perforations

3/16 x 2 1/2



