WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6068
Rec. Aug. 21 1961
Well No.
Permit No.
Do not fill in

Owner: Ben Hallmark Driller: J.C. Farello & Son

Address: 582 Broadway Blvd. Reno, Nev Address: 736 Humboldt St, Reno Lic. No. 2

Location of well: ____¼____¼ Sec. 13, T. 19 N/S, R. 19 E, in Truckee Meadows, Washoe County

or East of Wells Avenue 3 blocks. 582 Broadway Blvd., Reno, Nev.

Water will be used for: Domestic & Irrigation Total depth of well: 80 ft.

Size of drilled hole: 6 inch Weight of casing per linear foot: 12.89 Lbs.

Thickness of casing: .188 of an inch Temp. of water: 70°

Diameter and length of casing: 6 5/8" O.D. 11'-06" to 11'-09" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 14'-03"

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: July 21, 1961 Date of completion of well: August 7, 1961

Type of well rig: Speed Star 71 Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Yellow clay with fine to coarse sand & coarse gravel. Rocky & stony. 17 ft. Boulder.
25	30	5	Fine to coarse sand & gravel, rocks, stony. 30 ft. Boulder.
33	36	3	1st water. Water. Water level 19'-10". Fine to coarse sand & gravel. Sand Heaves.
36	40	4	Sand & rocks. Hard.
40	50	10	2nd water. Fine to coarse sand. Rocks.
50	60	10	3rd water. Water level 14'-04". Sand & rocks. 53 ft. Boulder.
60	64	4	Sand & rocks. Sand Heaves.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 64 to 80 ft.

Other aquifers: 50 to 60
33 to 36

First water at 33 feet.

Casing perforated
from ____ to ____ ft.

Size of perforations

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
64	80	16	4th water. Clay stratas with small veins of fine to medium sand between. Few pebbles. Soft.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8"	0'-06"	68'-09"	69'-03"	6 5/8" O.D. Blackpipe. Welded with 1/4"x3" couplings. Short pattern drive shoe. Grouts made with puddled clay.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

From 0 to 64 ft. sand material tan colored, light + some black. 64 to 80 ft material gray black color. Material washed + smooth. Cleaned + bailed well 17gal per minute 35ft. bailing level. Well is clean to 80ft. no sand running in.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated August 16, 1961

(Not to be filled in by Driller)

1961 AUG 21 AM 9 49

STATE ENGINEER