

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 6078  
 Rec. Aug 23 1961  
 Well No. 1  
 Permit No. 19054

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Herbert Goss Driller Paul Taylor #11 Broadway  
 Address P.R.T. Julia Texas Address Plainsview Texas Lic. No. 346  
 Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec 28, T 3 N/S, R 55 E, in Lincoln County  
 or South E Corner E half, 57 miles out Hwy #25 from Warm Springs  
 Water will be used for Irrigation + Domestic Total depth of well Pilot Hole 300' 250'  
 Size of drilled hole 18" Weight of casing per linear foot 40 #  
 Thickness of casing 1/4" Temp. of water see test report later  
 Diameter and length of casing 16 x 251'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure No.  
 If nonflowing well give depth of standing water from surface 76'  
 If flowing well describe control works None (Type and size of valve, etc.)  
 Date of commencement of well July Aug 15 Date of completion of well Aug 17  
 Type of well rig \_\_\_\_\_

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Top soil
6	16	10	Large Gravel small Rock
16	90	74	Med Gravel fine sand
90	104	14	Soft formation same returns
104	163	59	small gravel + sand
163	251	88	Fine gravel + coarse sand
251	300	49	Pilot Hole fine gravel + coarse sand

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 90 to 300 ft.

Other aquifers \_\_\_\_\_

No change in type of gravel + sand same color + size to 300' Pilot Hole

First water at 76 feet.

Casing perforated

from 89 to 251 ft.

Size of perforations

3/16 x 10' x 20' Centers 4 rows

