Log No. 61285
Rec. SEPT 18 19 61
Well No.
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Julius Ballardini Driller: J.C. Farettol & Son

Address: 4200 Lone Tree Lane, Reno, Nev. Address: 736 Humboldt St. Reno Lic. No. 2

Location of well: NW 1/4 NW 1/4 Sec. 11, T. 18 N/S, R. 19 E, in Truckee Meadows, Washoe County

or 3/4 miles west from Lakeside Drive on Lone Tree Lane, (Lone Tree Ranch)

Water will be used for: Domestic Total depth of well: 113'-00"

Size of drilled hole: 6 inch Weight of casing per linear foot: 12.89 Lbs.

Thickness of casing: .188 of an inch Temp. of water: 62°

Diameter and length of casing: 6 5/8" O.D. 10'-00" to 20'-00" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 25'-00"

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: August 18, 1961 Date of completion of well: September 6, 1961

Type of well rig: Speed Star 71 Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Hardpan.
10	40	30	Yellow clay with coarse sand + gravel.
40	52	12	1st. water. Water level 23'-08". Little water. Fine to coarse sand + gravel. Loose.
52	57	5	Yellow clay with sand.
57	75	18	2nd water. Not too much water. Red clay with fine to coarse sand. Soft, Tight.
75	86	11	3rd. water. Little water. Red clay with fine to coarse sand.
86	90	6	Rock ledge. Pink granite. Soft.
90	92	2	Fine sand. Gray colored granite sand.
92	100	8	4th water. Not much water. Red clay with pink colored sand. Soft, Tight.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 100 to 105 ft.

Other aquifers: 75 to 86
40 to 52

First water at 40 feet.

Casing perforated

from 75 to 86 ft.

Size of perforations

919