# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

**PLEASE COMPLETE THIS FORM IN ITS ENTIRETY**

Log No. 6213
Rec. Nov. 3 1961
Well No.
Permit No.
*Do not fill in*

Owner Harry Swanson, Sr. Driller A & B Contractors (G. Rahier)

Address Reno, Nev. Address Sun Valley, Nev. Lic. No 343

Location of well: NE 1/4 SE 1/4 Sec. 19, T20 N/S, R 20 E, in Washoe County

or

Water will be used for domestic Total depth of well 83'

Size of drilled hole 6" Weight of casing per linear foot 12 lbs

Thickness of casing 188 ga. Temp. of water cold

Diameter and length of casing 6" X 80'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 20'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 6-1-61 Date of completion of well 6-3-61

Type of well rig x cable tool

## LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|---|---|---|---|
| 0 | 30 | 30 | dug well |
| 30 | 65 | 35 | sandy clay |
| 65 | 83 | 18 | brown sand |

**Water-bearing Formation, Casing Perforations, Etc.**

Chief aquifer (water-bearing formation)

from ..... to ..... ft.

Other aquifers

First water at 36 feet.

Casing perforated

from 66 to 76 ft.

Size of perforations

1/8 x 6"

(OVER)

919

## LOG OF FORMATIONS—*Continued*

| From feet | To feet | Thickness | Type of material |
|---|---|---|---|
| | | | |

## CASING RECORD

| Diam. casing | From feet | To feet | Length | "Remarks"—Seals, Grouting, Etc. |
|---|---|---|---|---|
| 6-5/8 | 1 | 0 | 83 | 188 ga;welded joints;clay and sandy clay grout |

## GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail test 15 GPM; 20'DD

## WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A & B Contractors
Well Driller

By M. Cattles

License No. 1538

Dated Nov 1, 1961

(Not to be filled in by Driller)