WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 2532
Rec. 10/3 1961
Well No.
Permit No.
Do not fill in

Owner Rudy Talucci Driller A & B Contractors (G. Rahier)

Address W 7th St, Reno, Nev Address Sun Valley, Nev Lic. No. 343

Location of well: SE ¼ SW ¼ Sec 4, T 20 N/S/ R 19 E, in Washoe County

or

Water will be used for domestic Total depth of well 205

Size of drilled hole 6" Weight of casing per linear foot 13 lbs

Thickness of casing ¼" Temp. of water cold

Diameter and length of casing 6" X 205'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 68'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Date of completion of well

Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	68	68	clay & brown rock
68	69	1	sand & gravel
69	185	116	clay
185	191	6	gravel
191	205	14	weathered granite

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 68 to 69 ft.

Other aquifers 185-191

First water at 68 feet.

Casing perforated
from 143 to 205 ft.

Size of perforations
1/8 X 6"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6	1	0	205	gravel pack at perforations; clay grout; spring drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

20 GPM; 140' DD

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A. J. R. Construction
Well Driller

By M. Martin

License No. 5598

Dated Nov 1, 1961

(Not to be filled in by Driller)

NOV 3 AM 8 43
1961

STATE ENGINEER
SANTA FE