

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 6300
 Rec. Nov. 28 1961
 Well No. 3
 Permit No. 16833
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY
A Co. Partnership

Owner Donald T. & Peggy Hall/ Driller Lukin Bros.

Address Zephyr Cove, Nevada Address Tahoe Valley, Calif. Lic. No. _____

Location of well: NW 1/4 NE 1/4 Sec. 26, T. 13N/S, R. 18E, in M.D.B.&.M. Lake Tahoe, Douglas County
 or _____

Water will be used for Quasi-Municipal Total depth of well 124 feet

Size of drilled hole 8" Weight of casing per linear foot _____

Thickness of casing 1/8" Temp. of water 45°

Diameter and length of casing 8" - cemented to 50'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 20'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well July, 1956 Date of completion of well Sept. 20, 1956

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
Surface	30'	30'	Soft Granite
30'	60'	30'	Red Granite
60'	90'	30'	Hard White Granite
90'	124'	34'	Layer of coarse granite and gravel

Water-bearing Formation, Casing Perforations, Etc.
None to 90'

Chief aquifer (water-bearing formation)

from 90' to 124' ft.

Other aquifers _____

First water at 90' feet.

Casing perforated
solid to 50'

from _____ to _____ ft.

No perforations

Size of perforations _____



