Need Copy

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 6319
Rec. Dec 18 1961
Well No.
Permit No.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in

Owner: Stauffer Chemical Co. 636 California St., San Francisco 8, California

Driller: S.R. McKinney & Sons, Inc. 1042 So. Main

Address: Address: Clark Lic. No. 45

Location of well: ~~NE¼ SE¼ T17S R68E~~ Near Overton boat dock, S 23, T 17 N/S, R 68 E, in County

or SE Sec. 23 T17S, R68E

Water will be used for: Industrial purposes 211 feet

Total depth of well: 12" = ¼ wall, 8" = ¼ wall

Size of drilled hole: 12" = ¼ wall, 8" = ¼ wall

Weight of casing per linear foot:

Thickness of casing: 12 3/4" O.D. to 209 feet, 8 5/8" O.D. to 211 feet.

Temp. of water:

Diameter and length of casing:
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: 102.2 feet

If nonflowing well give depth of standing water from surface: Well capped

If flowing well describe control works:

Date of commencement of well: 10/3/61 (Type and size of valve, etc.) 11/21/61

Date of completion of well: Dacyrus Erie 24L

Type of well rig:

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Material
0	40	40	sand & gravel
40	48	8	sand & little gravel
48	65	17	sand & gravel
65	70	5	sand & little gravel
70	80	10	sand
80	86	6	sand & gravel
86	87	1	cement gravel
87	90	3	gravel & sand
90	97	7	sand
97	105	8	gravel & sand
105	110	5	clay sand & gravel (water)
110	111	1	cement gravel
111	114	3	sandy clay & gravel
114	118	4	sand (water)
118	143	25	sand & gravel (~~[illegible]~~) Water
143	156	13	sandstone
156	162	6	quick sand (water)
162	170	8	gravel & sand cemented
170	181	11	clay & sand
181	182	1	sticky clay
182	192	10	sand stone
192	193	11	sticky clay
193	206	13	sand stone
206	211	5	sand stone

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation) 118 [illegible]

from 105 to 110 ft.

Other aquifers

105

First water at feet.

Casing perforated 12" = 57 [illegible]
8" = 114 to 211 ft.

from to ft.

12" = 125 mesh, 27 slots
6" centers, 12 rows.

8" = 125 mesh, 2" slots
6" centers, 10 rows.

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
12"3/4 O.D.	0	209	209	Well is gravel packed between 12" casing & 8" casing with pea gravel.
8 5/8"O.D.	0	211	211	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump tested 300 G.P.M. from 119'-6" Little Sand

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed S.R. McKinney & Sons, Inc.

By

M.R. McKinney No. [illegible]

Dated [illegible] 19[illegible]

(Not to be filled in by Driller)

1967 DEC 18 AM 10 46

STATE ENGINEER