23150

Log No. 6325
Rec. DEC. 21 1961
Well No.
Permit No. 23156
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: PINE PARKS CORP. Driller: Loyd Lee Bennett

Address: Denio, Nevada Address: Denio, Nevada Lic. No. Applied For

Location of well: SE ¼ SW ¼ Sec. 15, T. 47 N/S, R. 30 E, in Humboldt County

or

Water will be used for: Irrigation Total depth of well: 356'

Size of drilled hole: 16" Weight of casing per linear foot: Approx. 21 lbs.

Thickness of casing: 188 ga. Temp. of water: 68 degrees

Diameter and length of casing: 16" O.D. 356'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: Static water level 41'.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: Aug. 10, 1961 Date of completion of well: Sept. 21, 1961

Type of well rig: Cable Tool 24-L Bucyrus Erie

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18"	18"	Top Soil
18"	26"	8"	hard Pan
26"	68'	64' 10"	Dry Gravel with soil
68'	156'	88'	Decomposed Granite 5/8-
156'	168'	12'	Sticky Clay
168'	290'	122'	Decomposed Granite 5/8-
290'	350'	60'	Large water Gravel 3/4-
350'	356'	6'	Sticky Clay

Plugged by Well Log No. 116351 under NOI 67118

Replaced by well log # 116350

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 290 to 350 ft.

Other aquifers 68' to 156'

168' to 290'

First water at 68 feet.

Casing perforated

from 68' to 347 ft.

Size of perforations

Width 3/8" Length 3"
Mills Perforator

(OVER)

919