WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 6367
Rec. FEB. 6 1962
Well No.
Permit No.
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Edmond Coveau Driller: F. R. Baxter
Address: Washoe Valley Address: Carson City Lic. No. 322
Location of well: NW1/4 NW1/4 Sec. 24, T. 17 N/S, R. 19 E, in Washoe County
or

Water will be used for: Home Total depth of well: 80
Size of drilled hole: 8 5/8" Weight of casing per linear foot: 9.5
Thickness of casing: 10 ga. Temp. of water: normal
Diameter and length of casing: 6 1/4 x 80
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:
If nonflowing well give depth of standing water from surface: 21'
If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Oct 6, 61 Date of completion of well: Oct 8, 61
Type of well rig: Rotary Potta-Drill 500

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Top soil
5	37	32	cemented gravel
37	41	4	blue clay
41	55	14	fine sand
55	80	25	coarse sand and small rocks

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 55 to 80 ft.

Other aquifers

First water at 41 feet.

Casing perforated
from 60 to 80 ft.

Size of perforations
3/8"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 1/4	0	80	80	8 5/8 hole drilled and casing set Hole around casing filled with 1/4" gravel to surface

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed F. R. Barker
Well Driller

By R. Johnson

License No. 322

Dated Jan 31, 1962

(Not to be filled in by Driller)