18-96-7
1875-8-7

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 6369
Rec. Nov 28 19 62
Well No. 2
Permit No.
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Donald T. & Peggy Hall/ A co-Partnership Driller: Lukins Bros.

Address: Zephyr Cove, Nevada Address: Tahoe Valley, Calif. Lic. No.

Location of well: SE ¼ SW¼ Sec. 23, T 13 N/S, R 18 E, in Douglas County

or

Water will be used for: Quasi-Municipal Total depth of well: 130'

Size of drilled hole: 10" Weight of casing per linear foot:

Thickness of casing: 1/8" Temp. of water: 45°

Diameter and length of casing: 10" to 70'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 24'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Sept., 1956 Date of completion of well: Oct., 1956

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0'	70'	70'	Red Granite
70'	100'	30'	White Granite
100'	130'	30'	Gravel and Rock

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 100' to 130' ft.

Other aquifers

First water at 100' feet.

Casing perforated
from to ft.

Solid casing to 70'
Size of perforations
No perforations

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0'	70'	70'	Solid casing with shoe driven into solid rock granite

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well pumped to clear water 24 hours.

Very good water - no sand.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible]
Well Driller

By [illegible]

License No. [illegible]

Dated [illegible], 19[illegible]

(Not to be filled in by Driller)