Basin #108 4B

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6394
Rec. Feb 9 19 62
Well No.
Permit No. 18672
Do not fill in

Owner: Mr. and Mrs J.P. Peeples, Jr. Driller: R. D. Ogden

Address: Rt. 2 Box 10, Yerington, Nev. Address: Box 162, Yerington, Nev. Lic. No.

Location of well: E½ ~~NE¼~~ ~~NW¼~~ Sec. 16, T. 14N/~~S~~, R. 25E, in M.D.B. & M. County

or

Water will be used for: Irrigation and Domestic Total depth of well: 225 feet

Size of drilled hole: ~~16 inch~~ 24 inch Weight of casing per linear foot:

Thickness of casing: 188 Temp. of water:

Diameter and length of casing: 16 inch 225 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 9 feet

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: June 1, 1960 Date of completion of well: July 2, 1960

Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	Sand
30	90	60	Coarse sand
90	117	27	Clay
117	127	10	Fine sand
127	139	12	Clay
139	179	40	Coarse sand
179	196	17	Black clay
196	225	29	Coarse gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 30 to 225 ft.

Other aquifers: 139

First water at 30 feet.

Casing perforated
from 100 ft. to 225 ft.

Size of perforations
1/8 by 10 inch slits

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Tested 1785 G.P.M. at 62 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [signature] Well Driller

By

License No. 315

Dated 7/2, 1960

(Not to be filled in by Driller)