

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6412
 Rec. Mar. 5 19 62
 Well No.
 Permit No.
Do not fill in

Owner Frank E. Skinner Driller Pete Anderson

Address 701 Lot Head Hotel Address Box 85 Steamboat Lic. No. 307

Location of well: SE 1/4 NW 1/4 Sec. 31, T. 17 N/S, R. 20 E, in Washoe County

or Block J, Lot 3 New Washoe City #5 890-386-82

Water will be used for Domestic Total depth of well 80'

Size of drilled hole 6" Weight of casing per linear foot 13#

Thickness of casing 3/16 in. 188 well Temp. of water Cool

Diameter and length of casing 6 inches to 70'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. None flow

If nonflowing well give depth of standing water from surface. 24 ft.

If flowing well describe control works.
(Type and size of valve, etc.)

Date of commencement of well Feb 20, 1962 Date of completion of well Feb 24, 1962

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	5'		loose sand	
5	20'		sandy clay	Chief aquifer (water-bearing formation)
20'	30'		sand	from <u>50'</u> to <u>70'</u> ft.
30'	50'		blue sand + mud	Other aquifers <u>25 to 30 ft</u>
50'	70'		blue sand + gravel	
70'	80'		solid formation of granite	
				First water at <u>25</u> feet.
				Casing perforated
				from <u>60'</u> to <u>70'</u> ft.
				Size of perforations
				<u>1/8" x 4"</u>



