


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 6418  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. 2827357329  
*Do not fill in*

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

CNLV- FRANK GOWEN WELL # I Owner  
 Driller HOLDERS & CRIBB 70  
 Address 10 30 franklin Av. Address 2710 palomino Lane Lic. No. 156  
 Location of well: NE 1/4 NW 1/4 Sec. 18, T. 20N/S, R. 6E, in \_\_\_\_\_ County  
 or east of saltlake high way and south of cheyenne road PERMIT NO. 57329  
 Water will be used for domestic Total depth of well 700 ft.  
 Size of drilled hole 10 8 5/8 Weight of casing per linear foot 10 Ga.  
 Thickness of casing 3.26 Temp. of water \_\_\_\_\_  
 Diameter and length of casing random  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure pump test 850 G.P.M.  
 If nonflowing well give depth of standing water from surface 86  
 If flowing well describe control works PUM P  
(Type and size of valve, etc.)  
 Date of commencement of well feb 6 Date of completion of well feb 22 1961  
 Type of well rig spudder

### LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material   | Water-bearing Formation, Casing Perforations, Etc.                            |
|-----------|---------|----------------|--|---|
|           |         |                | This well drilled to 550 ft<br>14 in hole 10 in. well casing<br>packed with gravel and tested<br>for 180 G.P.M.s | Chief aquifer (water-bearing formation)<br>485 440<br>from _____ to _____ ft. |
| 350       | 435     | 85             | pink sandy clay  | Other aquifers <u>575</u>   |
| 435       | 440     | 5              | broken rock and gravel at top  |   |
| 440       | 525     | 85             | pink sandy clay  |   |
| 525       | 528     | 3              | gravel and decomposed limestone<br>some water  |   |
| 528       | 550     |                | red clay caving  | First water at _____ feet.  |
| 550       | 700     | 150            | yellow clay sticky<br>no water below 525   |   |
|           |         |                | This 8 5/8 liner is gravel<br>packed from 440 to 550 ft<br>in pea gravel   | Casing perforated<br>from 350 to 550 ft.                                      |
|           |         |                | good water bearing strata<br>from 485 to 440   | Size of perforations<br><u>1/4 x 6 in</u>                                     |

LOG OF FORMATIONS—Continued

| From feet | To feet | Thickness | Type of material |
|-----------|---------|-----------|------------------|
|           |         |           |                  |

-CASING RECORD

| Diam. casing | From feet | To feet | Length | "Remarks"—Seals, Grouting, Etc. |
|--------------|-----------|---------|--------|---------------------------------|
|              |           |         |        |                                 |

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

---



---



---



---



---

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Charlie Culler  
Well Driller

By S. R. Rodgini

License No. 70 : 156

Dated Feb 22, 1962

(Not to be filled in by Driller)

---



---



---



---



---



---



---



---



---



---