

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6438
 Rec. Mar 29 1962
 Well No. _____
 Permit No. 17677
Do not fill in

Owner Morna Records. Driller E. V. Weimer.

Address 508 Irene St. Bakersfield, Calif. Address Lathrop's Well, Nevada. Lic. No. 171.

Location of well: S. E. 1/4 SE 1/4 Sec. 26, T. 6 N. S. R. 7 E, in Eye County
 or _____

Water will be used for Domestic purposes. Total depth of well 300 ft.

Size of drilled hole 12" Weight of casing per linear foot 28.07 #

Thickness of casing 1/4" Temp. of water 68 degrees.

Diameter and length of casing 10 3/4" O. D. To 300'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 120 Ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 2/25/61 Date of completion of well 3/25/61.

Type of well rig Cable Tool.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	6	6	Top Soil.	
6	15	9	Tight soil.	
15	22	7	Hard lime cap.	Chief aquifer (water-bearing formation) from _____ to _____ ft.
22	40	18	Light colored clay.	Other aquifers _____
40	90	50	Brown, or reddish clay.	_____
90	140	50	Light clay, with an occasional hard streak, every 2 or 3 Ft.	_____
140	280	140	Light colored clay with laminations of sand and gravel.	_____
280	300	20	Sticky bentonitic clay.	_____

First water at 142 Ft feet.

Casing perforated from 140 ft. to 300 ft.

Size of perforations 1/8" x 2"

