Need Copy

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 6475
Rec. April 19 1962
Well No.
Permit No. 19228
Do not fill in

Owner: Victor A. Kunz
Address: 532 West Sycamore Ave El Segundo, Calif.
Driller: Stanley Ford
Address: Stanley Ford Lic. No. 47
Location of well: NE ¼ NW ¼ Sec. 14, T21 N/S, R53 E, in Nye County
or Permit No 19228
Water will be used for: Irrigation
Total depth of well: 400
Size of drilled hole: 16 in
Weight of casing per linear foot:
Thickness of casing: 1/4 in
Temp. of water:
Diameter and length of casing: 14 in
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure:
If nonflowing well give depth of standing water from surface: 25 ft
If flowing well describe control works:
(Type and size of valve, etc.)
Date of commencement of well: Dec 9-61
Date of completion of well: Dec 25-62
Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	16	16	Clay
16	21	5	caliche
21	90	9	Clay
90	143	53	lime-water
143	270	127	Clay
270	272	2	lime
272	276	4	Clay
276	350	74	lime-water
350	381	31	Clay
381	385	4	lime
385	392	7	Clay
392	400	8	lime

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 90 to 143 ft.
Other aquifers 276-350

First water at 28 feet.

Casing perforated
from 28 to 400 ft.

Size of perforations
3/8 in

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
14	0	400	400	Cemented from 0 to 12 ft

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump test about 1000 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Stanley Ford
Well Driller

By

License No. 47

Dated April 10, 1962

(Not to be filled in by Driller)

OFFICE
STATE ENGINEER
1962 APR 19 AM 8 56