

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6482
 Rec. April 24 1962
 Well No. _____
 Permit No. 18787
Do not fill in

Owner W.T. Jones 2131 Rollingwood Drive Driller Dave McIninch
 Address San Bruno, California Address Winnemucca, Nevada Lic. No. 219

Location of well: SE 1/4 SE 1/4 Sec. 29., T.26.N/S, R.43.E, in Lander County
 or _____

Water will be used for Irrigation Total depth of well 240

Size of drilled hole 17 Weight of casing per linear foot 30#

Thickness of casing 10 ga. Temp. of water cold

Diameter and length of casing 16 1/2 x 240
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. _____

If nonflowing well give depth of standing water from surface 58

If flowing well describe control works. _____
(Type and size of valve, etc.)

Date of commencement of well May 15, 1961 Date of completion of well July 25, 1961

Type of well rig 71 Speed Star Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	4	4	Sandy Clay topsoil	
4	9	5	Tight Clay	
9	56	47	Dry Broken Gravel	
56	105	49	Clay and Gravel	Chief aquifer (water-bearing formation)
105	108	3	Soft White Clay	from <u>188</u> to <u>240</u> ft.
108	124	16	Clean Loose Gravel	Other aquifers <u>All loose</u>
124	146	22	Sandy Clay and Gravel Seams	<u>seams of gravel &</u>
146	158	12	Clean Loose gravel	<u>sand.</u>
158	174	16	Sand and Gravel	
174	188	14	Clay	
188	240	62	Large Clean Gravel	First water at <u>108</u> feet.
240	244	4	Sticky Clay	
				Casing perforated
				from <u>108</u> to <u>240</u> ft.
				Size of perforations
				<u>1/4 x 23/4" slots</u>

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16	0	240	240	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well was tested with 160' 8" turbine pump. Delivers 2000 gpm from 110 ft. water is very clean and cold. Pump test was run for 8 hours steady.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Dave McNinch
Well Driller

By *Dave McNinch*

License No. 219

Dated April 22, 19 62

(Not to be filled in by Driller)

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

OFFICE
STATE ENGINEER
1962 APR 24 AM 9 13

187378

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

✓ Log No. 6482
 Rec. April 24 1962
 Well No. _____
 Permit No. 18737
Do not fill in

Owner W.T. Jones Driller Dave McNinch

Address 2131 Coltingwood Drive San Bruno, California Address Winnemucca, Nevada Lic. No. 219

Location of well: SE 1/4 SE 1/4 Sec. 29., T. 26. N/S, R. 43. E, in Lander County _____
 or _____

Water will be used for Irrigation Total depth of well 240

Size of drilled hole 17 Weight of casing per linear foot 30#

Thickness of casing 10 ga. Temp. of water cold

Diameter and length of casing 16 1/2 x 2401
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 38

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well May 25, 1961 Date of completion of well July 25, 1961

Type of well rig 71 Speed Star Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Sandy Clay topsoil
4	9	5	Tight Clay
9	56	47	Dry Broken Gravel
56	105	49	Clay and Gravel
105	108	3	Soft White Clay
108	124	16	Clean Loose Gravel
124	146	22	Sandy Clay and Gravel Seams
146	158	12	Clean Loose gravel
158	174	16	Sand and Gravel
174	188	14	Clay
188	240	62	Large Clean Gravel
240	244	4	Sticky Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 188 to 240 ft.

Other aquifers All loose seams of gravel & sand.

First water at 108 feet.

Casing perforated from 108 to 240 ft.

Size of perforations 1/4 x 23/4" slots



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	Remarks—Seals, Grouting, Etc.
16	0	240	240	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well was tested with 160' 8" turbine pump. Delivers 2000 gpm from 110 ft. water is very clean and cold. Pump test was run for 8 hours steady.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Dave McNinch
Well Driller

By Dave McNinch

License No. 219

Dated April 22, 19 62

(Not to be filled in by Driller)

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

OFFICE OF
STATE ENGINEER
APR 24 AM 9 13