Log No. 6557
Rec. May 29 1962
Well No.
Permit No. 20273
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Need Copy

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Robert Levoff Driller Douglas Slayle

Address 1814 S. Sixth St LV Address P.O. Box 2081-LV Lic. No. 137

Location of well: N.W. ¼ S.W. ¼ Sec. 28, T. 21 S/S, R. 61 E, in Clark County

or ½ mile So. of Bond Rd & ½ mile East of L.A. Highway on Lot # 96

Water will be used for Domestic & Commercial Total depth of well 200 ft

Size of drilled hole 14" for 10" casing Weight of casing per linear foot

Thickness of casing .203 Temp. of water 60° approx

Diameter and length of casing 10.406" x 200 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure —

If nonflowing well give depth of standing water from surface 26 ft

If flowing well describe control works —
(Type and size of valve, etc.)

Date of commencement of well May 10 1961 Date of completion of well Appx May 17 1961

Type of well rig Buckrus-Erie - 29T -

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	Gypsum & Gravel
7	16	9	Calcho
16	21	5	White clay
21	24	3	Water Gravel - Sand
24	28	4	Calcho
28	35	7	Light Brown Clay
35	36	1	Sheet of Rock
36	56	20	Red Clay
56	68	12	Light Brn Clay & Gravel
68	72	4	Solid Rock
72	78	6	Water Gravel & Sand
78	100	22	Light Br. Clay
100	112	12	Red Sticky soft Clay
112	125	13	Lt Brn, Clay, Gravel & Water
125	127	2	Sheet Rock Solid
127	137	10	Red Sandy Clay
137	140	3	Solid Rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 180' to 187' ft.

Other aquifers 112'-125'
72'-78'
21'-24'

First water at 21 feet.

Casing perforated

from 60' to 200' ft.

Size of perforations

3/16 x 1½ and ⅛ x 8" approx

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
40	146	6	Greenish, Slimmy Clay
46	175	29	Red Sticky Soft Clay
75	180	5	Hard solid Rock
80	187	7	Water, Sand, gravel, clay,
87	195	8	~~Wh~~ Cream Colored Clay, Sand
95	199	4	White Clay
99	200	1	Solid Rock
			Stopped drilling at 200 ~~[illegible]~~ still in solid Rock

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
0" I.D.	0'	160'	160'	3 sacks of pure cement ~~used~~ as seal at bottom to hold gravel - in event of well deeped in future - gravel packed to 51 ft - cemented with 6 ~~[illegible]~~ WMK, pea gravel grout - 51' to 0' = using 3½ yds of grout
0" O.D.	160'	200'	40'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

10 bailers in 10 minutes = 210 gallons total - Static level at 26 ft pulled down to 60 ft - 20 minutes to recover to 29 ft Static level

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Douglas Slagle
Well Driller

By Douglas Slagle

License No. 137

Dated June 26, 1961

(Not to be filled in by Driller)

OFFICE
STATE ENGINEER
1962 MAY 29 AM 9 24