

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6578
 Rec. June 11 1962
 Well No. _____
 Permit No. 19251
Do not fill in

Owner John Boynton & Mr. & Mrs. Henry P. Harrer Driller George Etchart

Address Winnemucca, Nevada Address Winnemucca, Nevada Lic. No. 355

Location of well: SE 1/4 NE 1/4 Sec. 2, T. 35N/S, R. 37E, in Humboldt County

Water will be used for Irrigation & Domestic Total depth of well 155 Ft.

Size of drilled hole 12" Weight of casing per linear foot 25 lbs.

Thickness of casing 3/16" Temp. of water Cold
sand screen

Diameter and length of casing 155 Ft. 12" DD x 3/16" casing, 152 Ft. 11" ID perforated liner, 5' sand
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 11 Ft.

If flowing well describe control works.....
 (Type and size of valve, etc.)

Date of commencement of well July 7, 1961 Date of completion of well May 23, 1962

Type of well rig Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Sandy soil
8	20	12	Quick sand
20	25 35	35	Quick sand with pea gravel
55	80	25	Quick sand
80	85	5	Clay and sand
85	97	12	Very wild sand
97	105	8	Gravel w/some clay
105	155	50	Sandy gravel, mostly sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 11 to 155 ft.

Other aquifers.....

First water at 11 feet.

Casing perforated

from 30 to 155 ft.

Size of perforations

3/8" x 2 1/2"
152 Ft. 11" ID sand screen

