

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6664  
 Rec. July 27 1962  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Gil Sanchez Driller W. L. McDonald

Address 679 Apple St.; Reno, Nevada Address 669 Apple St.; Reno, Nev. Lic. No. 363

Location of well:  $\frac{1}{4}$  Sec. 7, T. 4N/S, R. 20E, in Washoe County  
 or Portion of lot 1A, Block B of Fairview Farms Sub., Corner of  
or Fairview and Dryden Dr. off Holcomb Ln.

Water will be used for domestic purposes Total depth of well 140 ft.

Size of drilled hole 8 in. Weight of casing per linear foot 156 wall line pipe

Thickness of casing 156 wall Temp. of water cold

Diameter and length of casing 8 5/8" random lengths  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 76'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well June 2, 1962 Date of completion of well June 4, 1962

Type of well rig Bucyrus Erie 24-L

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	17	17	Brown sandy topsoil	
17	60	43	Yellow sandy clay with inconsistent gravels to 1"	Chief aquifer (water-bearing formation) from <u>97</u> to <u>135</u> ft.
60	85	25	Sand & gravels to 1"-some silt	Other aquifers _____
85	97	12	Brown sandy clay	
97	135	38	Brown sandy clay with alternate streaks of sand and gravels to 1/2"	
135	140	5	Brown sandy clay	
				First water at <u>88</u> feet.
				Casing perforated from <u>95</u> to <u>135</u> ft.
				Size of perforations <u>1/8" by 6"</u>



