Log No. 6677
Rec. Aug 13 1962
Well No.
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Primo Quarisa — Driller: Harold J. Faretto

Address: 13000 Sage Hill Rd., Reno, Nev. — Address: 736 Humboldt St., Reno — Lic. No. 2

Location of well: NE¼ SW¼ Sec. 21, T. 18 N/S, R. 20 E, in Truckee Meadows, Washoe County

or ¼ mile east from Reno-Carson Hwy or east from Brown's School.

Water will be used for: Domestic — Total depth of well: 65'-00"

Size of drilled hole: 6 inch — Weight of casing per linear foot: 12.89 lbs.

Thickness of casing: .188 of an inch — Temp. of water: 112°

Diameter and length of casing: 6 5/8" O.D. Diameter, 9'-06" to 22'-00" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 37'-10"

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: July 13, 1962 — Date of completion of well: July 19, 1962

Type of well rig: Speed Star 71 Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	27	27	Hardpan
27	45	18	Clay with fine to coarse granite sand.
45	50	5	1st. water, Water temperature 98°, Water level 34'-00", Fine to coarse sand with clay.
50	55	5	2nd. water, Water level 37'-00", Fine to coarse sand & gravel with clay.
55	65	10	3rd water, Fine to coarse sand & gravel with yellow clay.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 55 to 65 ft.

Other aquifers:

First water at 45 feet.

Casing perforated
from ..... to ..... ft.

Size of perforations

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8"	1'-00"	59'-00"	60'-00"	6 5/8" O.D. Black pipe, Welded with 1/4"x3" couplings. 1/4"x6" iron band used as drive shoe. Grouted to 40ft. with cement.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Sand & gravel material granite. Gravel shows washed conditions. Hot water zone. Cleaned & bailed well 10 gal per minute 2 ft drawdown.
Tried to keep water at a low temperature & still have a moderate yield of water.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harold J. Faretto
Well Driller

By

License No. 2

Dated August 1, 1962

(Not to be filled in by Driller)

1962 AUG 13 AM 10 07