


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 6710  
 Rec. Sept 7 1962  
 Well No. \_\_\_\_\_  
 Permit No. 19399  
*Do not fill in*



Owner Milo Mileusnich Driller S. R. McKinney & Son

Address R. R. 1, Box 38, Las Vegas, Nevada Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NE 1/4 NE 1/4 Sec. 23, T. 21 N/S, R. 61 E, in Clark County

Water will be used for Domestic & Motel/Comm. Total depth of well 190

Size of drilled hole 12" to 55 ft, 10" to 190 Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 190 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 8 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Jan. 27, 1956 Date of completion of well Jan. 30, 1956

Type of well rig Bucyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	soil and clay
3	5	2	gravel
5	14	9	caliche
14	52	38	sandy clay
52	55	3	gravel water
55	65	10	sandy clay
65	70	5	sand and clay water
70	115	45	sandy clay
115	125	10	clay and gravel
125	160	35	sandy clay
160	165	5	clay and gravel
165	172	7	sandy clay
172	180	8	sand and clay water
180	190	10	sand and gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 180 to 190 ft.

Other aquifers 172 to 180

65 to 70

First water at 52 feet.

Casing perforated from 150 to 190 ft.

Size of perforations 3/16" X 10"

