

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 6832
 Rec. Nov. 7 1962
 Well No. _____
 Permit No. 20004
Do not fill in

Owner William Harrah Driller Nevada Pump & Irr. Co., Inc.

Address 995 Crummer Lane Reno, Nevada Address RFD 1 Box 457 Reno, Nev. Lic. No. 6648A

Location of well: 1/4 SE 1/4 Sec. 36, T. 19N/S, R. 19E, in Washoe County
 or _____

Water will be used for Irrigation Total depth of well 245 Ft.

Size of drilled hole 24 inch Weight of casing per linear foot 33.63

Thickness of casing .250 Temp. of water Cold

Diameter and length of casing 12 3/4" O.D. 245 Ft. Len.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure No

If nonflowing well give depth of standing water from surface 3 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Sept. 14, 1962 Date of completion of well October 15, 1962

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Top Soil
10	20	10	Top soil and sand
20	30	10	Sand
30	40	10	Boulders and gravel
40	50	10	Gravel
50	80	30	Sand and 1/8" Gravel
80	110	30	Sand and 1/4" Gravel
110	120	10	Sand and 1/8" Gravel
120	130	10	Sand and 1/4" Gravel
130	140	10	Sand
140	170	30	Sand and 1/8" Gravel
170	180	10	Sand, 1/8" Gravel & Clay
180	190	10	Sand, 1/4" Gravel & Clay
190	200	10	Sand, 1/8" Gravel & Clay
220	230	10	Sand and 1/8" Gravel
230	245	15	Clay and Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 45 to 125 ft.
 from 160 to 230 ft.

Other aquifers _____

First water at 15 feet.

Casing perforated
 from 45 to 125 ft.
 from 150 to 230 ft.

Size of perforations
1/8" X 2" Machine Cut.



