

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 6846
 Rec. Nov 16 1962
 Well No. _____
 Permit No. _____
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner W. H. Eubank Driller George Etchart

Address Colconda, Nevada Address Winnemucca, Nevada Lic. No. 355

Location of well: 1/4 NE 1/4 Sec. 22, T. 39(N)S, R. 31E, in Humboldt County
 or One mile east of Etchart Ranch in Gum Boot Lake area. (Approx. 18 miles NE of Winnemucca.)

Water will be used for Stock watering Total depth of well 50 ft.

Size of drilled hole 10" Weight of casing per linear foot 28 lbs.

Thickness of casing 3/16" Temp. of water Cold

Diameter and length of casing 10" x 50 Ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 16 1/2 Ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well November 8, 1962 Date of completion of well November 13, 1962

Type of well rig Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Soil
12	27	15	Blocky clay
27	32	5	Clean wash gravel w/water
32	41	9	Brown sand
41	50	9	Dry sand and gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 27 to 32 ft.

Other aquifers _____

First water at 27 feet.

Casing perforated
 from 27 to 32 ft.

Size of perforations
3/8" x 2"

