

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

✓ Log No. 6884
 Rec. DEC. 3. 1962
 Well No.
 Permit No.
Do not fill in

Owner Airbase Mobile Home Village Driller Reno Pump & Supply

Address Black Springs, Nevada Address 7468 So. Virginia - Reno Lic. No. 295

Location of well: SW 1/4 NW 1/4 Sec. 37, T. 20 N/S, R. 19 E, in Washoe County

Water will be used for Domestic - Trailer Court Total depth of well 272'

Size of drilled hole 8" Weight of casing per linear foot

Thickness of casing .188" Wall Temp. of water Cold

Diameter and length of casing 8" x ~~222~~ 262'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 65'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well 6/26/61 Date of completion of well 8/6/61

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Clay & Rocks
18	47	29	Sandy Clay
47	51	4	Cube rock
51	78	27	Brown clay
78	86	8	Clay & gravel
86	98	12	Broken rock
98	120	22	Brown clay
120	122	2	Gravel with some water
122	133	11	Brown clay
133	136	3	Gravel, some water
136	145	9	Sticky Brown clay
145	150	5	Clay & gravel mixed
150	197	47	Brown Clay
197	203	6	Red Clay
203	207	4	Green Clay
207	210	3	Red Gravel & clay
210	240	30	Gravel & Water
240	243	3	Brown Clay
243	250	7	Red sticky slay
250	255	5	Red gravel & clay
255	262	7	Gravel & water
262	272	10	Rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 210 to 240 ft.

Other aquifers

See Log

First water at 120 feet.

Casing perforated
None

from to ft.

Size of perforations

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	262	262'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail tests @ 20 GPM from 205' pumping water level. 140' drawdown from 65' Static Water Level.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Rene Pump & Supply
Well Driller

By Harry W. Jones
License No. 295

Dated Aug. 8, 1961

(Not to be filled in by Driller)

Seal fax Appl 1-7-63

1962 DEC 3 PM 4 07

STATE ENGINEER
OFFICE