

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6893
 Rec. DEC. 4 1962
 Well No. _____
 Permit No. 18810
Do not fill in

Owner A. J. Seelig Driller Dave McKinch

Address Box 486 Battle Mtn. Nevada Address Box 588 Winnemucca, Nev. Lic. No. 217

Location of well: SE 1/4 SW 1/4 Sec. 10, T. 26N/S, R. 42E, in Lander County
 or _____

Water will be used for Irrigation Total depth of well 300

Size of drilled hole 17 1/2 Weight of casing per linear foot 30#

Thickness of casing 16 ga. Temp. of water Cold

Diameter and length of casing 16 1/2 x 300
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 75'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Nov. 1, 1962 Date of completion of well Nov. 11, 1962

Type of well rig #71 Speed Star Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Sandy clay topsoil
12	20	8	Big broken dry gravel
20	57	37	Clay
57	80	23	Fine dry gravel with clay
80	82	2	Sticky clay
82	97	15	Clean fine gravel, loose
97	121	24	Hard clay
121	160	39	Fine gravel clay seams
160	195	35	Fine loose gravel
195	245	50	Clay with gravel seams
245	300	55	Large loose gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 245 to 300 ft.

Other aquifers All loose gravel seams

First water at 82 feet.

Casing perforated from 80 to 300 ft.

Size of perforations

5/16 x 3" slots
Approx. 25 per ft.



