

20795-
20796

Deepened by well Log # 110653

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

ADDRES

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6984
 Rec. JAN 17 19 63
 Well No.
 Permit No. 20990
Do not fill in

Owner North American Aviation Co. Driller Enloe Drilling Co.

Address Reno, Nev. Address Carson City, Nev. Lic. No. 247

Location of well: SE NE ~~NE~~ 1/4 Sec. 6, T22 N/S, R. 21 E, in Washoe County

or APN 496-242-05 Palomino Unit 5 6.2.1.4 part A

Water will be used for Industrial Total depth of well 500

Size of drilled hole 24" to 375 ft, 12" - 500 Weight of casing per linear foot 19

Thickness of casing 10 Ga Kai-well Temp. of water

Diameter and length of casing 12" 375 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 93 ft

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well Oct, 62. Date of completion of well Dec, 62

Type of well rig Rotary.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Topsoil.
6	8	2	Gravel
8	105	97	Conglomerate, clay, gravels
105	120	15	Medium Sand.
120	185	65	Yellow Clay.
185	220	35	Medium Sand & Boulders.
220	230	10	Coarse Granite Sand
230	295	65	Brown Clay & Boulders.
295	307	12	Sandy Clay
307	334	27	Brown Clay.
334	357	23	Sand & Clay.
357	365	8	Medium Sand.
365	500	135	Blue Clays.

*NAD 27 GPS
39.805261°N
119.659040°W*

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 105 to 365 ft.

Other aquifers

First water at 105 feet.

Casing perforated
from 120 to 375 ft.

Size of perforations
3/16X2 Factory.

