

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 7018  
 Rec. Feb 15 1963  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Mr Woodrow Eriksen Driller Walgamott & Son  
 Address Orovada Nevada Address 1026 Winnemucca Nev. Lic. No. 292  
 Location of well: NE 1/4 NE 1/4 Sec. 5, T41 N/S, R 37 E, in Humboldt County \_\_\_\_\_  
 or \_\_\_\_\_  
 Water will be used for Stock Well Total depth of well 74ft.  
 Size of drilled hole 10 inch Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing ~~10 1/2 O.D.~~ 3/16 Temp. of water \_\_\_\_\_  
 Diameter and length of casing 10 1/2 O.D.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 22 ft.  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Nov. 1, 1962 Date of completion of well Nov. 11, 1962  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Dry Rock, Sand
3	14	11	Dry Sand
14	23	9	Sandy Clay
23	33	10	Hard Clay
33	38	5	Sand & Gravel
38	43	5	Soft Brown Clay
43	58	15	Packed Sand
58	67	9	Brown Clay
67	<del>80</del> 74	<del>13</del> 7	Sand & Gravel

~~\_\_\_\_\_~~  
 [Well came in to 74 ft.]

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 33 to 38 ft.  
 Other aquifers 67 80  
74

---

First water at 34 feet.

---

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

---

Size of perforations \_\_\_\_\_

