WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7027
Rec. Feb. 20 19 63
Well No. 1
Permit No. 23694 Do not fill in
Basin 057

Owner: Clyde Henson
Driller: Robert F Hodges
Address:
Address: Battle Mtn
Lic. No. 320

Location of well: SE of North ½ ¼ ¼ Sec. 10, T 24 N/S, R 40 E, in Lander County
or N 39.969787 W 117.452548 NAD27

Water will be used for: Farming
Total depth of well: 260
Size of drilled hole: 17 3/4"
Weight of casing per linear foot: 24
Thickness of casing: 10 ga Knuell
Temp. of water: 56
Diameter and length of casing: 4' X 16 4"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: Not tested

If nonflowing well give depth of standing water from surface:

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Nov 22, 1962
Date of completion of well: Dec 8, 1962

Type of well rig: 3000 Franks

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1'	8'	8'	Top soil
8	28	20	gravel
28	80	68	gravel clay
80			water
80	116	36	clean pea gravel
116	152	36	gravel streaks clay
152	170	18	Gravel sand tall clay
170	198	28	streak clay
198	224	26	sandy clay
224	240	16	Gravel clay
240	260	20	clay gravel very fine sand

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 80 to 244 ft.

Other aquifers

First water at 77 feet.

Casing perforated
from 80 to 244 ft.

Size of perforations
1/4

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16"			4'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Robert L Hodges
Well Driller

By

License No. 320

Dated Feb 19, 1963

(Not to be filled in by Driller)