Log No. 7074
Rec. 19
Well No.
Permit No. 20431
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

(Las Vegas Valley Water Dist)

Owner Wastrn Industries, Inc. Driller John R. Beylik

Address 920 S. Main St., Las Vegas, Nevada Address 11118 Luitweiler Ave., Whittier, Calif. Lic. No. 575

Location of well: NE ¼ NW ¼ Sec. 28, T. 21 N/S, R 61 E, in Clark County

or

Water will be used for Domestic + Commercial Total depth of well 905

Size of drilled hole 24" Weight of casing per linear foot 33 lbs.

Thickness of casing 1/4" Temp. of water ?

Diameter and length of casing 12" Inside Dia. x 1/4" Wall
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 39'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Nov. 26, 1962 Date of completion of well Feb. 15, 1963

Type of well rig Reverse Circulation Rotary Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Caliche Clay
3	54	51	Cemented Gravel
51	90	39	Sand & Gravel to 2" diam.
90	190	100	Hard Sand Clay
190	260=	70	Grazel & Thin Layers of Cemented Gravel
260	270	10	Gravel
270	300	30	Hard Clay
300	360	60	Caliche and Gravel (Hard)
360	370	10	Cemented Gravel (Hard)
370	522=	152	Hard Dry clay
522	540	18	Caliche Gravel (loose) water
540	550	10	Hard Packed Sand (Fine)
550	570	20	Hard Dry Clay
570	630	60	Cemented gravel
630	660	30	Loose coarse gravel and sand

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 630 to 900 ft.

Other aquifers 210-230

350-370

First water at 12 feet.

Casing perforated

from 200 to 315 ft.

340-370 --610-900

Size of perforations

1/8 x 2-1/2 Louver

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
660	810	150	Sand and gravel-thin layers of clay
810	820	10	Clay
820	830	10	Gravel
830	850	20	Hard Clay
850	870	20	Clay and gravel
870	900	30	Gravel - semi-cemented
900	905	5	Hard clay and gravel

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
26"	0	54	54	26" casin g was cemented in a 32" drill hole 0- to 54'
12"	0	900	900	Casing is 12 3/4" O.D. x 1/4" Wall

FORMATION—Pumping Test, Quality of Water, Etc.

Pre-perforated casing was installed 610 to 900 ft. — Well produced 420 gals. per min. from 300 ft. Well was then perforated from 200 to 315 ft. and 340 to 370 ft. Well produced 900 gals. per min. from 240 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed John R. Beylik
Well Driller

By John R. Beylik
John R. Beylik, Owner
License No. 375

Dated March 13, 19 63

(Not to be filled in by Driller)

RECEIVED
MAR 19 1963
DIV. OF WATER RESOURCES
BRANCH OFFICE
LAS VEGAS, NEVADA