

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7076
 Rec. Mar. 31 1963
 Well No.
 Permit No.

Do not fill in

Owner Quinn Municipal & Domestic Driller N & S well service

Address Reno Address Black spr. no-Lic. No 696

Location of well: NE 1/4 SE 1/4 Sec 16, T 20 N/S, R 19 E, in Washoe County

Water will be used for Domestic Total depth of well 284'

Size of drilled hole 8 3/4" Weight of casing per linear foot 188

Thickness of casing 188 Temp. of water cold

Diameter and length of casing ~~6 1/4"~~ 6 1/4" 284'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface ~~117'~~

If flowing well describe control works.....
(Type and size of valve, etc.)

Date of commencement of well 1-28-63 Date of completion of well 2-28-63

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	70	70	soft shale Brown	
70	80	10	Gravel medium	Chief aquifer (water-bearing formation)
80	100	190	soft Brown shale	from <u>190'</u> to <u>225'</u> ft.
190	225	35	with thin layers of hard Brown shale	Other aquifers 225 to 284'
			Gravel medium water Bearing	
225	245	20	Sand stone Gray water Bearing	First water at <u>190</u> feet.
245	260	15	Blue shale Hard	
260	284	24	Gray sand stone water Bearing	Casing perforated from <u>144</u> to <u>284</u> ft.
				Size of perforations <u>well 3/16 x 12</u>

