


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 7130  
 Rec. April 15 1963  
 Well No. \_\_\_\_\_  
 Permit No. 19393

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner CRYSTAL BAY DEVELOPMENT CO. Driller Same  
 Address Box 207 Incline village Address Crystal Bay Nevada Lic. No. \_\_\_\_\_  
 Location of well: NE 1/4 NE 1/4 Sec. 10, T. 16 N/S, R. 18 E, in Washoe County \_\_\_\_\_ County  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 225

Size of drilled hole 24.3" Weight of casing per linear foot \_\_\_\_\_

Thickness of casing .31 Temp. of water 39°

Diameter and length of casing 24.38" x 22' plus perforated sand casing 8"  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure 330 at c.f.s. at 10 lbs.

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works flows constantly until 8" float valve demands  
(Type and size of valve, etc.)

Date of commencement of well July 1960 Date of completion of well \_\_\_\_\_ and structure Oct. 60

Type of well rig Surface Auger 36" C. P.

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10'	10'	Glacial moraine
10	22'	12'	Volcanics
22	30'	8'	Volcanics

#### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 18 to 30 ft.

Other aquifers \_\_\_\_\_

First water at 12 feet.

Casing perforated  
 from 22' to 30' ft.

Size of perforations  
1/8" 1 1/4"



