

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7146
 Rec. MAY 13 1963
 Well No. _____
 Permit No. 19421
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Judge E. CONST. Driller J. B. Pappalardo
 Address FOLLON Address Yallahua NW Lic. No. 28
 Location of well: NW 1/4 NW 1/4 Sec 36, T. 19 N/S, R. 47 E, in Lander County
at a point from which the N.W. Cor. Sec. 36 T. 19 N Range 47 E. M.D.B.E.M. bears N 83° 13' 55" W,
or 514.70 ft distant
 Water will be used for Highway Construction Total depth of well 102'
 Size of drilled hole 8" Weight of casing per linear foot 18 lbs
 Thickness of casing 1.88 Temp. of water Cold
 Diameter and length of casing 8" X 102'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 56 feet
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well April 21 1958 Date of completion of well April 28 - 58
 Type of well rig Shurn drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	24	24	Gravel.
24	27	3	Clay.
27	66	39	Sand & gravel.
66	69	3	Gray clay.
69	92	23	Gravel & sand.
92	102	10	Gravel & clay.
102	113	11	Water gravel.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 102 to 113 ft.

Other aquifers _____
69:92

First water at 69 feet.

Casing perforated
 from 69 to 116 ft.

Size of perforations
Mills Knife

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. B. Reynolds
Well Driller

By _____

License No. 28

Dated April 29, 1958

(Not to be filled in by Driller)

1963 MAY 10 AM 9 33

STATE ENGINEER
OFFICE