WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7176
Rec. May 20 19 63
Well No.
Permit No.
Do not fill in

Owner: Frank Foote
Driller: Smith & Pulati Inc.
Address:
Address: 195-26th Ave Sparks Lic. No. 207 208

Location of well: ¼ ¼ Sec. 30, T. 17 N/S, R. 20 E, in MDB+M Washoe County

or

Water will be used for: Domestic
Total depth of well:

Size of drilled hole: 6 5/8
Weight of casing per linear foot: 1.289

Thickness of casing: .188
Temp. of water:

Diameter and length of casing: 6 5/8 OD by 101 Long.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 62

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 4-22
Date of completion of well: 4-25-63

Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Top Soil
8	48	40	Clay + Gravel
48	70	22	Decomposed Gravel
70	92	18	Tight Sand
92	100	9	Sand + Water.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 90 to 100 ft.

Other aquifers:

First water at 70 feet.

Casing perforated
from 80 to 96 ft.

Size of perforations
1/16 x 6 4 Rows

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8	~~101~~ 0	101	101	Weld Black Line pipe Steel Shoe Neat Grout Seal 21 feet

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Static Water Level 62
Bailed 25 G.P.M.
Drawdown 75 ft

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Smith Pump Inc
Well Driller

By Claude Smith

License No. 207

Dated 4-25, 19 63

(Not to be filled in by Driller)

1963 MAY 20 AM 9 22
STATE ENGINEER
OFFICE